

# Conformance Statements for WSRF-ResourceProperties 1.2

## **Author:**

Kam K. Yee – IBM Corporation

## **Statements:**

**Conformance Statement ID:** WSRF\_RP\_0001

**Conformance Statement Description:**

**Category:** WSDL

**Line #:** 328

**Description:**

If a resource properties document contains resource properties, its definition MUST be a complexType defining a collection of zero or more child elements, each of these child elements defining a resource property element. Each resource property element MUST be defined in XML Schema as a GED.

**Conformance Statement ID:** WSRF\_RP\_0002

**Conformance Statement Description:**

**Category:** WSDL

**Line #:** 356

**Description:**

Any interface that includes a resource properties document type declaration (/wsdl:portType/@ResourceProperties) MUST also include the GetResourceProperty message exchange (operation).

**Conformance Statement ID:** WSRF\_RP\_0003

**Conformance Statement Description:**

**Category:** Message

**Line #:** 364

**Description:**

The format of the GetResourcePropertyDocument request message MUST conform to the following schema:

```
<xsd:element name="GetResourcePropertyDocument">  
  <xsd:complexType/>  
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0004

**Conformance Statement Description:**

**Category:** Message

**Line #:** 366

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsf/>

[/rpw-2/GetResourcePropertyDocument/GetResourcePropertyDocumentRequest](http://docs.oasis-open.org/wsf/rpw-2/GetResourcePropertyDocument/GetResourcePropertyDocumentRequest).

**Conformance Statement ID:** WSRF\_RP\_0005

**Conformance Statement Description:**

**Category:** Message

**Line #:** 369

**Description:**

The format of the response to the GetResourcePropertyDocument request message MUST conform to the following schema:

```
<xsd:element name="GetResourcePropertyDocumentResponse">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:any minOccurs="1" maxOccurs="1"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0006

**Conformance Statement Description:**

**Category:** Message

**Line #:** 374

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsf>

[/rpw-2/GetResourcePropertyDocument/GetResourcePropertyDocumentResponse](http://docs.oasis-open.org/wsf/rpw-2/GetResourcePropertyDocument/GetResourcePropertyDocumentResponse).

**Conformance Statement ID:** WSRF\_RP\_0007

**Conformance Statement Description:**

**Category:** Message

**Line #:** 451

**Description:**

The format of the GetResourceProperty request message MUST conform to the following schema:

```
<xsd:element name="GetResourceProperty"
  type="xsd:QName" />
```

**Conformance Statement ID:** WSRF\_RP\_0008

**Conformance Statement Description:**

**Category:** Message

**Line #:** 457

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsf>

[/rpw-2/GetResourceProperty/GetResourcePropertyRequest](http://docs.oasis-open.org/wsf/rpw-2/GetResourceProperty/GetResourcePropertyRequest).

**Conformance Statement ID:** WSRF\_RP\_0009

**Conformance Statement Description:**

**Category:** Message

**Line #:** 464

**Description:**

The format of the response to the GetResourceProperty request message MUST conform to the following schema:

```
<xsd:element name="GetResourcePropertyResponse" >
  <xsd:complexType>
    <xsd:sequence>
      <xsd:any minOccurs="0" maxOccurs="unbounded" />
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0010

**Conformance Statement Description:**

**Category:** Message

**Line #:** 470

**Description:**

The wsa:Action MUST contain the URI:  
<http://docs.oasis-open.org/wsrp/rpw-2/GetResourceProperty/GetResourcePropertyResponse>.

**Conformance Statement ID:** WSRF\_RP\_0011

**Conformance Statement Description:**

**Category:** Message

**Line #:** 528

**Description:**

The format of the GetMultipleResourceProperties request message MUST conform to the following schema:

```
<xsd:element name="GetMultipleResourceProperties">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element name="ResourceProperty" type="xsd:QName"
        minOccurs="1" maxOccurs="unbounded" />
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0012

**Conformance Statement Description:**

**Category:** Message

**Line #:** 532

**Description:**

The wsa:Action MUST contain the URI:  
<http://docs.oasis-open.org/wsrp/rpw-2/GetMultipleResourceProperties/GetMultipleResourcePropertiesRequest>.

**Conformance Statement ID:** WSRF\_RP\_0013

**Conformance Statement Description:**

**Category:** Message

**Line #:** 541

**Description:**

The format of the response to the GetMultipleResourceProperties request message MUST conform to the following schema:

```
<xsd:element name="GetMultipleResourcePropertiesResponse">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:any minOccurs="0" maxOccurs="unbounded" />
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0014

**Conformance Statement Description:**

**Category:** Message

**Line #:** 546

**Description:**

The wsa:Action MUST contain the URI:  
<http://docs.oasis-open.org/wsrp/rpw-2/GetMultipleResourceProperties/GetMultipleResourcePropertiesResponse>.

**Conformance Statement ID:** WSRF\_RP\_0015

**Conformance Statement Description:**

**Category:** Message

**Line #:** 635

**Description:**

The format of the QueryResourceProperties request message MUST conform to the following schema:

```
<xsd:element name="QueryResourceProperties" >
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="wsrf-rp:QueryExpression"
        minOccurs="1" maxOccurs="1"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0016

**Conformance Statement Description:**

**Category:** Message

**Line #:** 641

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsrp>

[/rpw-2/QueryResourceProperties/QueryResourcePropertiesRequest](http://docs.oasis-open.org/wsrp/2/QueryResourceProperties/QueryResourcePropertiesRequest).

**Conformance Statement ID:** WSRF\_RP\_0017

**Conformance Statement Description:**

**Category:** Message

**Line #:** 655

**Description:**

If the attribute */wsrf-rp:QueryResourceProperties/wsrf-rp:QueryExpression/@Dialect* in a QueryResourceProperties request message had a value of "<http://www.w3.org/TR/1999/REC-xpath-19991116>" (the well-known URI identifying the expression dialect to be an XPath [XPath] language expression), the contents of the QueryExpression MUST be a string containing a valid XPath 1.0 expression.

**Conformance Statement ID:** WSRF\_RP\_0018

**Conformance Statement Description:**

**Category:** WSDL

**Line #:** 669

**Description:**

A WS-Resource that supports the QueryResourceProperties message exchange MUST support QueryExpressions that contain a Dialect with value "<http://www.w3.org/TR/1999/REC-xpath-19991116>".

**Conformance Statement ID:** WSRF\_RP\_0019

**Conformance Statement Description:**

**Category:** Message

**Line #:** 676

**Description:**

The format of the response to the QueryResourceProperties request message MUST conform to the following schema:

```

<xsd:element name="QueryResourcePropertiesResponse" >
  <xsd:complexType>
    <xsd:complexContent mixed="true">
      <xsd:restriction base="xsd:anyType">
        <xsd:sequence>
          <xsd:any processContents="lax"
            minOccurs="1" maxOccurs="unbounded"/>
        </xsd:sequence>
      </xsd:restriction>
    </xsd:complexContent>
  </xsd:complexType>
</xsd:element>

```

**Conformance Statement ID:** WSRF\_RP\_0020

**Conformance Statement Description:**

**Category:** Message

**Line #:** 681

**Description:**

The wsra:Action MUST contain the URI:

<http://docs.oasis-open.org/wsrp>

[/rpw-2/QueryResourceProperties/QueryResourcePropertiesResponse](http://docs.oasis-open.org/wsrp/2/QueryResourceProperties/QueryResourcePropertiesResponse).

**Conformance Statement ID:** WSRF\_RP\_0021

**Conformance Statement Description:**

**Category:** Message + WSDL

**Line #:** 708

**Description:**

If a WS-Resource supports the QueryResourceProperty operation (checked in the WSDL) *and supports dialects in addition to the required XPath 1.0 dialect* (checked in the Message), then it MUST include a wsrf-rp:QueryExpressionDialect resource property within its resource property document definition (checked in the WSDL). Such a WS-Resource MAY include this resource property if it supports only the XPath 1.0 dialect.

**Conformance Statement ID:** WSRF\_RP\_0022

**Conformance Statement Description:**

**Category:** WSDL

**Line #:** 711

**Description:**

The form of the wsrf-rp:QueryExpressionDialect resource property is:

```

<xsd:element name="QueryExpressionDialect" type="xsd:anyURI"/>

```

Furthermore, this reference MUST reflect the minOccurs and maxOccurs properties as follows:

```

<xsd:element ref="wsrf-rp:QueryExpressionDialect"
  minOccurs="0" maxOccurs="unbounded" />

```

**Conformance Statement ID:** WSRF\_RP\_0023

**Conformance Statement Description:**

**Category:** Message

**Line #:** 771

**Description:**

The format of the PutResourcePropertyDocument request message MUST conform to the following schema:

```
<xsd:element name="PutResourcePropertyDocument">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:any minOccurs="1" maxOccurs="1"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0024

**Conformance Statement Description:**

**Category:** Message

**Line #:** 775

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsf>

[/rpw-2/PutResourcePropertyDocument/PutResourcePropertyDocumentRequest](http://docs.oasis-open.org/wsf/rpw-2/PutResourcePropertyDocument/PutResourcePropertyDocumentRequest).

**Conformance Statement ID:** WSRF\_RP\_0025

**Conformance Statement Description:**

**Category:** Message

**Line #:** 785

**Description:**

The format of the response to the PutResourcePropertyDocument request message MUST conform to the following schema:

```
<xsd:element name="PutResourcePropertyDocumentResponse">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:any minOccurs="0" maxOccurs="1"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0026

**Conformance Statement Description:**

**Category:** Message

**Line #:** 790

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsf>

[/rpw-2/PutResourcePropertyDocument/PutResourcePropertyDocumentResponse](http://docs.oasis-open.org/wsf/rpw-2/PutResourcePropertyDocument/PutResourcePropertyDocumentResponse).

**Conformance Statement ID:** WSRF\_RP\_0027

**Conformance Statement Description:**

**Category:** Message

**Line #:** 874

**Description:**

The format of the SetResourceProperties request message MUST conform to the following schema:

```
<xsd:element name="SetResourceProperties">
  <xsd:complexType>
    <xsd:choice minOccurs="1" maxOccurs="unbounded">
      <xsd:element ref="wsrf-rp:Insert"/>
      <xsd:element ref="wsrf-rp:Update"/>
      <xsd:element ref="wsrf-rp:Delete"/>
    </xsd:choice>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0028

**Conformance Statement Description:**

**Category:** Message

**Line #:** 888

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsrp/rpw-2/SetResourceProperties/SetResourcePropertiesRequest>.

**Conformance Statement ID:** WSRF\_RP\_0029

**Conformance Statement Description:**

**Category:** Message

**Line #:** 956

**Description:**

The format of the response to the SetResourceProperties request message MUST conform to the following schema:

```
<xsd:element name="SetResourcePropertiesResponse" >
  <xsd:complexType />
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0030

**Conformance Statement Description:**

**Category:** Message

**Line #:** 960

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsrp/rpw-2/SetResourceProperties/SetResourcePropertiesResponse>.

**Conformance Statement ID:** WSRF\_RP\_0031

**Conformance Statement Description:**

**Category:** Message

**Line #:** 980

**Description:**

Any fault message indicating a failure during the update of the resource properties document (these fault messages are listed below) MUST also indicate whether the document was restored or not by using the ResourcePropertyChangeFailure element of the fault. This fault element indicates the resource property element change associated with the fault and indicates if the resource property document as a whole was restored. The format of this element is indicated as follows:

```

<xsd:complexType name="ResourcePropertyChangeFailureType">
  <xsd:sequence>
    <xsd:element name="CurrentValue" minOccurs="0" maxOccurs="1">
      <xsd:complexType>
        <xsd:sequence>
          <xsd:any minOccurs="1" maxOccurs="unbounded" />
        </xsd:sequence>
      </xsd:complexType>
    </xsd:element>
    <xsd:element name="RequestedValue" minOccurs="0" maxOccurs="1">
      <xsd:complexType>
        <xsd:sequence>
          <xsd:any minOccurs="1" maxOccurs="unbounded" />
        </xsd:sequence>
      </xsd:complexType>
    </xsd:element>
  </xsd:sequence>
  <xsd:attribute name="Restored" type="xsd:boolean"/>
</xsd:complexType>

```

UnableToPutResourcePropertyDocumentFault:

```

<xsd:complexType
  name="UnableToPutResourcePropertyDocumentFaultType">
  <xsd:complexContent>
    <xsd:extension base="wsrf-bf:BaseFaultType">
      <xsd:sequence>
        <xsd:element name="ResourcePropertyChangeFailure" type="
          wsrf-rp:ResourcePropertyChangeFailureType"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
<xsd:element name="UnableToPutResourcePropertyDocumentFault"
  type="
  wsrf-rp:UnableToPutResourcePropertyDocumentFaultType"/>

```

InvalidModificationFault:

```

<xsd:complexType
  name="InvalidModificationFaultType">
  <xsd:complexContent>
    <xsd:extension base="wsrf-bf:BaseFaultType">
      <xsd:sequence>
        <xsd:element name="ResourcePropertyChangeFailure" type=
          "wsrf-rp:ResourcePropertyChangeFailureType"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
<xsd:element name=
  "InvalidModificationFault"
  type=
  "wsrf-rp:InvalidModificationFaultType"/>

```

UnableToModifyResourcePropertyFault:

```

<xsd:complexType name="UnableToModifyResourcePropertyFaultType">
  <xsd:complexContent>
    <xsd:extension base="wsrf-bf:BaseFaultType">
      <xsd:sequence>
        <xsd:element name="ResourcePropertyChangeFailure" type=
          "wsrf-rp:ResourcePropertyChangeFailureType"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
<xsd:element name="UnableToModifyResourcePropertyFault"
  type="wsrf-rp:UnableToModifyResourcePropertyFaultType"/>

```

InvalidResourcePropertyQNameFault:

```

<xsd:complexType name="SetResourcePropertyRequestFailedFaultType">
  <xsd:complexContent>
    <xsd:extension base="wsrf-bf:BaseFaultType">
      <xsd:sequence>
        <xsd:element name="ResourcePropertyChangeFailure" type=
          "wsrf-rp:ResourcePropertyChangeFailureType"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
<xsd:element name="SetResourcePropertyRequestFailedFault"
  type=
  "wsrf-rp:SetResourcePropertyRequestFailedFaultType"/>

```

SetResourcePropertyRequestFailedFault:

```

<xsd:complexType name="SetResourcePropertyRequestFailedFaultType">
  <xsd:complexContent>
    <xsd:extension base="wsrf-bf:BaseFaultType">
      <xsd:sequence>
        <xsd:element name="ResourcePropertyChangeFailure" type=
          "wsrf-rp:ResourcePropertyChangeFailureType"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
<xsd:element name="SetResourcePropertyRequestFailedFault"
  type=
  "wsrf-rp:SetResourcePropertyRequestFailedFaultType"/>

```

InsertResourcePropertiesRequestFailedFault:

```

<xsd:complexType name="InsertResourcePropertiesRequestFailedFaultType">
  <xsd:complexContent>
    <xsd:extension base="wsrf-bf:BaseFaultType">
      <xsd:sequence>
        <xsd:element name="ResourcePropertyChangeFailure" type=
          "wsrf-rp:ResourcePropertyChangeFailureType"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
<xsd:element name="InsertResourcePropertiesRequestFailedFault"
  type=
  "wsrf-rp:InsertResourcePropertiesRequestFailedFaultType"/>

```

UpdateResourcePropertiesRequestFailedFault:

```

<xsd:complexType name="UpdateResourcePropertiesRequestFailedFaultType">
  <xsd:complexContent>
    <xsd:extension base="wsrf-bf:BaseFaultType">
      <xsd:sequence>
        <xsd:element name="ResourcePropertyChangeFailure" type=
          "wsrf-rp:ResourcePropertyChangeFailureType"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
<xsd:element
  name="UpdateResourcePropertiesRequestFailedFault"
  type="wsrf-rp:UpdateResourcePropertiesRequestFailedFaultType"/>

```

DeleteResourcePropertiesRequestFailedFault:

```

<xsd:complexType name="DeleteResourcePropertiesRequestFailedFaultType">
  <xsd:complexContent>
    <xsd:extension base="wsrf-bf:BaseFaultType">
      <xsd:sequence>
        <xsd:element name="ResourcePropertyChangeFailure" type="
          wsrf-rp:ResourcePropertyChangeFailureType"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
<xsd:element
  name="DeleteResourcePropertiesRequestFailedFault"
  type="wsrf-rp:DeleteResourcePropertiesRequestFailedFaultType"/>

```

**Conformance Statement ID:** WSRF\_RP\_0032

**Conformance Statement Description:**

**Category:** Message

**Line #:** 1076

**Description:**

The format of the InsertResourceProperties request message MUST conform to the following schema:

```

<xsd:element name="InsertResourceProperties">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="wsrf-rp:Insert"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>

```

**Conformance Statement ID:** WSRF\_RP\_0033

**Conformance Statement Description:**

**Category:** Message

**Line #:** 1082

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsrp/>

[/rpw-2/InsertResourceProperties/InsertResourcePropertiesRequest](http://docs.oasis-open.org/wsrp/2.0/InsertResourceProperties/InsertResourcePropertiesRequest).

**Conformance Statement ID:** WSRF\_RP\_0034

**Conformance Statement Description:**

**Category:** Message

**Line #:** 1103

**Description:**

The format of the response to the InsertResourceProperties request message MUST conform to the following schema:

```

<xsd:element name="InsertResourcePropertiesResponse" >
  <xsd:complexType />
</xsd:element>

```

**Conformance Statement ID:** WSRF\_RP\_0035

**Conformance Statement Description:**

**Category:** Message

**Line #:** 1107

**Description:**

The wsa:Action MUST contain the URI:  
<http://docs.oasis-open.org/wsrfl/rpw-2/InsertResourceProperties/InsertResourcePropertiesResponse>.

**Conformance Statement ID:** WSRF\_RP\_0036**Conformance Statement Description:****Category:** Message**Line #:** 1197**Description:**

The format of the UpdateResourceProperties request message MUST conform to the following schema:

```
<xsd:element name="UpdateResourceProperties">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="wsrf-rp:Update"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0037**Conformance Statement Description:****Category:** Message**Line #:** 1203**Description:**

The wsa:Action MUST contain the URI:  
<http://docs.oasis-open.org/wsrfl/rpw-2/UpdateResourceProperties/UpdateResourcePropertiesRequest>.

**Conformance Statement ID:** WSRF\_RP\_0038**Conformance Statement Description:****Category:** Message**Line #:** 1226**Description:**

The format of the response to the UpdateResourceProperties request message MUST conform to the following schema:

```
<xsd:element name="UpdateResourcePropertiesResponse" >
  <xsd:complexType />
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0039**Conformance Statement Description:****Category:** Message**Line #:** 1230**Description:**

The wsa:Action MUST contain the URI:  
<http://docs.oasis-open.org/wsrfl/rpw-2/UpdateResourceProperties/UpdateResourcePropertiesResponse>.

**Conformance Statement ID:** WSRF\_RP\_0040**Conformance Statement Description:****Category:** Message**Line #:** 1302**Description:**

The format of the DeleteResourceProperties request message MUST conform to the following schema:

```
<xsd:element name="DeleteResourceProperties">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="wsrf-rp:Delete"/>
    </xsd:sequence>
  </xsd:complexType>
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0041

**Conformance Statement Description:**

**Category:** Message

**Line #:** 1306

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsf/rpw-2/DeleteResourceProperties/DeleteResourcePropertiesRequest>.

**Conformance Statement ID:** WSRF\_RP\_0042

**Conformance Statement Description:**

**Category:** Message

**Line #:** 1321

**Description:**

The format of the response to the DeleteResourceProperties request message MUST conform to the following schema:

```
<xsd:element name="DeleteResourcePropertiesResponse" >
  <xsd:complexType />
</xsd:element>
```

**Conformance Statement ID:** WSRF\_RP\_0043

**Conformance Statement Description:**

**Category:** Message

**Line #:** 1325

**Description:**

The wsa:Action MUST contain the URI:

<http://docs.oasis-open.org/wsf/rpw-2/DeleteResourceProperties/DeleteResourcePropertiesResponse>.

**Conformance Statement ID:** WSRF\_RP\_0044

**Conformance Statement Description:**

**Category:** WSDL

**Line #:** 1403

**Description:**

If a WS-Resource supports the resource property value-change notification pattern, and if it uses WS-Notification to implement this feature, then it MUST implement the message exchanges for the NotificationProducer role, as specified in [WS-BaseNotification].

**Conformance Statement ID:** WSRF\_RP\_0045

**Conformance Statement Description:**

**Category:** Message

**Line #:** 1459

**Description:**

The `wsrf-rp:ResourcePropertyValueChangeNotification` element MUST appear as a component of the notification message associated with resource property value change topics. This element is defined as follows:

```
<xsd:complexType name="ResourcePropertyValueChangeNotificationType">
  <xsd:sequence>
    <xsd:element name="OldValues" nillable="true"
      minOccurs="0" maxOccurs="1" >
      <xsd:complexType>
        <xsd:sequence>
          <xsd:any minOccurs="1" maxOccurs="unbounded" />
        </xsd:sequence>
      </xsd:complexType>
    </xsd:element>
    <xsd:element name="NewValues" nillable="true"
      minOccurs="1" maxOccurs="1" >
      <xsd:complexType>
        <xsd:sequence>
          <xsd:any minOccurs="1" maxOccurs="unbounded" />
        </xsd:sequence>
      </xsd:complexType>
    </xsd:element>
  </xsd:sequence>
</xsd:complexType>

<xsd:element name="ResourcePropertyValueChangeNotification"
  type="wsrf-rp:ResourcePropertyValueChangeNotificationType" />
```